



# STOCK CHASER™

## EFFICIENTLY MANEUVER THROUGH YOUR WAREHOUSE.

Navigate narrow aisles and tight corners to retrieve and move cargo with the Stock Chaser. Maximize operational efficiency with the 9.6 sq ft cargo deck, 1,000-lb payload capacity, and 4 or 6-step ladder option for all your facility's needs.

**9.6 SQ FT**  
CARGO DECK CAPACITY

**4 OR 6**  
STEP LADDER OPTIONS

**DIAMOND-PLATED**  
STEEL



### OPTIONS & ACCESSORIES

- Pintle or “E” Hitch
- Counterweight
- Cargo Deck (Galvanized)
- Cargo Deck (Stainless Steel)
- Headlights and Taillights
- Forward Motion Indicator
- Side Rails
- Hour Meter
- State-of-Charge Meter
- Strobe Light (Ladder Required)
- Ladder – 4-Step (Counterweight Included)
- Ladder – 6-Step (Counterweight Included)

# STOCK CHASER

## BODY & CHASSIS

FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Diamond Plate Poly Primer and Acrylic
STANDARD COLOR	Safety Yellow

## DIMENSIONS

OVERALL LENGTH	88.4 in (225 cm)
OVERALL WIDTH	29.5 in (75 cm)
OVERALL HEIGHT	48.0 in (122 cm) (w/o Ladder) 78.0 in (198 cm) (w/ 4-step Ladder) 97.0 in (246 cm) (w/ 6-step Ladder)
WHEEL BASE	48.3 in (123 cm)
WHEEL TRACK	N/A Front / 24.75 in (63 cm) Rear
GROUND CLEARANCE	4.0 in (10 cm)
CARGO DECK CAPACITY	750.0 lb (340 kg)
CARGO DECK MATERIAL	Plywood

## POWER

POWER SOURCE	24V DC Series Wound
HORSEPOWER (KW)	8.94 hp (6.67 kW) @ 1490 rpm
ELECTRICAL SYSTEM	24V
BATTERY (QTY/TYPE)	Four, 6V Deep Cycle
BATTERY CHARGER	24V DC, 100-240V AC On-Board, UL & CE
KEY OR PEDAL START	Pedal
SPEED CONTROLLER	Solid State 275 Amp Rated
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	14.78:1

## PERFORMANCE

SEATING CAPACITY	1-Person (Standing)
WEIGHT W/O BATTERIES	522 lb (237 kg)
CURB WEIGHT	810 lb (367 kg)
VEHICLE LOAD CAPACITY	1000 lb (454 kg)
BED LOAD CAPACITY	750 lb (340 kg)
TOWING CAPACITY	Normal Draw Bar: 60 lb (27.2 kg) Max Draw Bar Pull: 715 lb (324 kg)
OUTSIDE CLEARANCE CIRCLE	12.4 ft (3.8 m)
SPEED	8.5 mph max (13.7 kph max)

## STEERING & SUSPENSION

STEERING	Direct Chain & Linkage
SUSPENSION	Solid (Front & Rear)
SERVICE BRAKE	Rear Wheel Mechanical Drum
PARKING BRAKE	Automatic
TIRES (FRONT & REAR)	4.80 x 8 (Load Range B)

**CUSHMAN.COM**

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. ©2024 Textron Specialized Vehicles Inc. 82328-G10 (Rev. 06/2024)

